



Part Number 10' LENGTHS	Part Number COILS	Part Number REELS	Trade Size	O.D.	I.D.
A51AE11Y 10' length	A51AEB1Y 200' length	A51AEQ1Y 1,500' length	1/2"	0.832" Min 0.848" Max	0.574" Min 0.630" Max
A51AG11Y 10' length	A51AGA1Y 100' length	A51AGJ1Y 1,000 length	3/4"	1.040" Min 1.060" Max	0.774" Min 0.834" Max
A51BA11Y 10' length	A51BAA1Y 100' length	A51BAN1Y 750' length	1"	1.305" Min 1.325" Max	0.999" Min 1.059" Max
A51BE11Y 10' length	Not Available	A51BEN1Y 750' length	1 1/2"	1.888" Min 1.912" Max	1.558" Min 1.622" Max

**ETL LISTED**

ETL CONTROL #3107144

CONFORMS TO UL1653

For use see NEC Article 362

Use only CANTEX No. 50 ENT Cement with this product

Not plenum rated

Blue & Red colors available

Not for exposed applications

May be used with SCH 40 PVC Couplings and fittings

600 Volt maximum

Not for direct bury

Minimum installation temperature -4°F (-20°C)

Maximum ambient temperature 122°F (50°C)

UL FT-4 Vertical Flame Test Rated



**EZ FLEX Type ENT Yellow**  
Electrical Nonmetallic Tubing

Drawn By: D. Gwinn

Date: 7/30/20

Ref. A51AE11Y