



Part Number 10' LENGTHS	Part Number COILS	Part Number REELS	Trade Size	O.D.	I.D.
A51AE11R 10' length	A51AEB1R 200' length	A51AEQ1R 1,500' length	1/2"	0.832" Min 0.848" Max	0.574" Min 0.630" Max
A51AG11R 10' length	A51AGA1R 100' length	A51AGJ1R 1,000 length	3/4"	1.040" Min 1.060" Max	0.774" Min 0.834" Max
A51BA11R 10' length	A51BAA1R 100' length	A51BAN1R 750' length	1"	1.305" Min 1.325" Max	0.999" Min 1.059" Max
A51BE11R 10' length	Not Available	A51BEN1R 750' length	1 1/2"	1.888" Min 1.912" Max	1.558" Min 1.622" Max

**ETL LISTED**

**ETL CONTROL #3107144**

**CONFORMS TO UL1653**

**For use see NEC Article 362**

**Use only CANTEX No. 50 ENT Cement with this product**

**Not plenum rated**

**Blue & Yellow colors available**

**Not for exposed applications**

**May be used with SCH 40 PVC Couplings and fittings**

**600 Volt maximum**

**Not for direct bury**

**Minimum installation temperature -4°F (-20°C)**

**Maximum ambient temperature 122°F (50°C)**

**UL FT-4 Vertical Flame Test Rated**



**EZ FLEX Type ENT Red  
Electrical Nonmetallic Tubing**

Drawn By: D. Gwinn

Date: 7/30/20

Ref. A51AE11R