



Part Number 10' LENGTHS	Part Number COILS	Part Number REELS	Trade Size	O.D.	I.D.
A51AE11 10' length	A51AEB1 200' length	A51AEQ1 1,500' length	1/2"	0.832" Min 0.848" Max	0.574" Min 0.630" Max
A51AG11 10' length	A51AGA1 100' length	A51AGJ1 1,000 length	3/4"	1.040" Min 1.060" Max	0.774" Min 0.834" Max
A51BA11 10' length	A51BAA1 100' length	A51BAN1 750' length	1"	1.305" Min 1.325" Max	0.999" Min 1.059" Max

**ETL LISTED**  
**ETL CONTROL #3107144**  
**CONFORMS TO UL1653**  
 For use see NEC Article 362  
 Use only CANTEX No. 50 ENT Cement with this product  
 Not plenum rated  
 Red & Yellow colors available upon request  
 Not for exposed applications  
 May be used with SCH 40 PVC Couplings and fittings  
 600 Volt maximum  
 Not for direct bury  
 Minimum installation temperature -4°F (-20°C)  
 Maximum ambient temperature 122°F (50°C)  
 UL FT-4 Vertical Flame Test Rated



<b>CANTEX</b> INC. Fort Worth, TEXAS		
<b>EZ FLEX Type ENT</b> Electrical Nonmetallic Tubing		
Drawn By: D. Gwinn	Date: 2/19/19	Ref. A51AE11