



Part Number 10' LENGTHS	Part Number COILS	Part Number REELS	Trade Size	O.D.	I.D.
A51AE11R 10' length	A51AEB1R 200' length	A51AEQ1R 1,500' length	1/2"	0.832" Min 0.848" Max	0.574" Min 0.630" Max
A51AG11R 10' length	A51AGA1R 100' length	A51AGJ1R 1,000 length	3/4"	1.040" Min 1.060" Max	0.774" Min 0.834" Max
A51BA11R 10' length	A51BAA1R 100' length	A51BAN1R 750' length	1"	1.305" Min 1.325" Max	0.999" Min 1.059" Max

**ETL LISTED**

ETL CONTROL #3107144

CONFORMS TO UL1653

For use see NEC Article 362

Use only CANTEX No. 50 ENT Cement with this product

Not plenum rated

Blue & Yellow colors available

Not for exposed applications

May be used with SCH 40 PVC Couplings and fittings

600 Volt maximum

Not for direct bury

Minimum installation temperature -4°F (-20°C)

Maximum ambient temperature 122°F (50°C)

UL FT-4 Vertical Flame Test Rated



**CANTEX**

INC.

Fort Worth, TEXAS

**EZ FLEX Type ENT Red**  
Electrical Nonmetallic Tubing

Drawn By: D. Gwinn

Date: 5/14/19

Ref. A51AE11R