



| Part Number | Size | T Min. | OD | ID Min. | E | B | D Min. | L Min. |
|-------------|--------|--------|--------|---------|--------|--------|--------|--------|
| A53AG42 | 3/4" | 0.154" | 1.050" | 0.698" | 1.064" | 1.046" | 1.750" | 240" |
| A53BA42 | 1" | 0.179" | 1.315" | 0.910" | 1.330" | 1.310" | 2.000" | 240" |
| A53BC42 | 1 1/4" | 0.191" | 1.660" | 1.227" | 1.677" | 1.655" | 2.250" | 240" |
| A53BE42 | 1 1/2" | 0.200" | 1.900" | 1.446" | 1.918" | 1.894" | 2.500" | 240" |
| A53CA42 | 2" | 0.218" | 2.375" | 1.881" | 2.393" | 2.369" | 3.000" | 240" |
| A53CE42 | 2 1/2" | 0.276" | 2.875" | 2.250" | 2.890" | 2.868" | 3.250" | 240" |
| A53DA42 | 3" | 0.300" | 3.500" | 2.820" | 3.515" | 3.492" | 3.750" | 240" |
| A53EA42 | 4" | 0.337" | 4.500" | 3.737" | 4.515" | 4.491" | 4.500" | 240" |
| A53FA42 | 5" | 0.375" | 5.563" | 4.713" | 5.593" | 5.553" | 5.500" | 240" |
| A53GA42 | 6" | 0.432" | 6.625" | 5.646" | 6.658" | 6.614" | 6.125" | 240" |

Dimensions are Nominal

ETL Listed
 Conforms to UL 651
 NEMA TC2 Compliant
 See NEC Article 352 for use
 Sunlight Resistant
 Max 90° C Wire



CANTEX
 INC.
 Fort Worth, TEXAS

Schedule 80 Rigid PVC Conduit

Drawn By: O.M.

Date: 5/22/17

Ref. A53AG42