



Part Number	Size	T Min.	OD	ID Min.	E	B	D Min.	L Min.
A60CA42	2"	0.154"	2.375"	2.021"	2.393"	2.369"	3.00"	240"
A60DA42	3"	0.216"	3.500"	3.008"	3.515"	3.492"	3.750"	240"
A60EA42	4"	0.237"	4.500"	3.961"	4.515"	4.491"	4.50"	240"
A60FA42	5"	0.258"	5.563"	4.975"	5.593"	5.553"	5.50"	240"
A60GA42	6"	0.280"	6.625"	5.986"	6.658"	6.614"	6.125"	240"

Dimensions are Nominal. See UL651 for tolerances.

CONFORMS TO NEMA TC2  
 SEE NEC Article 352 FOR US  
 NOT ETL/UL LISTED  
 MEETS MOST UL651 SPECIFICATIONS  
 MATERIAL IS RIGID PVC

Max 90° C Wire  
 Sunlight Resistant  
 Listed for exposed applications  
 Listed for direct bury  
 Listed for concrete encasement  
 Use approved PVC Cement for joining  
 Use proper equipment for field bending

**CANTEX**  
 INC.  
 Fort Worth, TEXAS

Cellular Foam Core Conduit

Drawn By: D. G. 3/16/20