



Part Number	Size	T Min.	OD	Øval.	E	B	D Min.	L Min.
A77BA42	1"	N/A	N/A	N/A	N/A	N/A	N/A	N/A
A77BE42	1 1/2"	N/A	N/A	N/A	N/A	N/A	N/A	N/A
A77CA42	2"	0.060"	2.375"	0.060"	2.396"	2.378"	1.750"	240"
A77DA42	3"	0.061"	3.500"	0.060"	3.529"	3.503"	2.875"	240"
A77EA42	4"	0.082"	4.500"	0.100"	4.533"	4.502"	3.375"	240"
A77FA42	5"	0.103"	5.563"	0.100"	5.601"	5.565"	4.000"	240"
A77GA42	6"	0.125"	6.625"	0.100"	6.669"	6.627"	5.000"	240"

Dimensions are Nominal.

ETL Listed
 Meets requirements of NEMA TC 6&8.
 Meets ASTM F-512.
 Material is Rigid PVC
 Bells are interference fit.
 Must be encased in concrete.
 Spigot I.D. is chamfered.

Complies with Federal and military specifications by conforming to UL 651



CANTEX
 INC.
 Fort Worth, TEXAS

EB-20 Rigid PVC Conduit
 High Modulus 500,000 psi

Drawn By: D.G.	1/2/19	A77BA42
----------------	--------	---------