



Part Number	Trade Size	Length	O.D.	I.D.
V06ADA1	3/8"	100' Coil	0.690" Min 0.710" Max	0.484" Min 0.504" Max
V06AEA1	1/2"	100' Coil	0.820" Min 0.840" Max	0.622" Min 0.642" Max
V06AGA1	3/4"	100' Coil	1.030" Min 1.050" Max	0.820" Min 0.840" Max
V06BAA1	1"	100' Coil	1.290" Min 1.315" Max	1.041" Min 1.066" Max
V06BCN1	1 1/4"	50' Coil	1.630" Min 1.660" Max	1.380" Min 1.410" Max
V06BEN1	1 1/2"	50' Coil	1.865" Min 1.900" Max	1.575" Min 1.600" Max
V06CAN1	2"	50' Coil	2.340" Min 2.375" Max	2.020" Min 2.045" Max
V06AEJ1	1/2"	1,000' Reel	0.820" Min 0.840" Max	0.622" Min 0.642" Max
V06AGM1	3/4"	700' Reel	1.030" Min 1.050" Max	0.820" Min 0.840" Max
V06BAD1	1"	400' Reel	1.290" Min 1.315" Max	1.041" Min 1.066" Max

UL Listed (UL1660)  
 UL Category Code DXDQ  
 CSA Listed  
 For Use See NEC Article 356  
 Do not use PVC Cement with this product,  
 use only approved liquidtight fittings  
 May be used outdoors exposed to sunlight  
 May be directly buried  
 600 volt maximum  
 Minimu installation temperature 0.4°F (-18°C)  
 Maximum ambient temperature 167°F (75°C)  
 UL Rated: 80°C dry, 60°C wet, 70°C oil resistant  
 Product is TYPE B LFNC  
 Not plenum rated

Dimensions are nominal



<b>CANTEX</b> INC. Fort Worth, TEXAS		
ENVIROFLEX Type LFNC-B Liquidtight Flexible Nonmetallic Conduit		
Drawn By: D. Gwinn	Date: 2/20/19	Ref. V06ADA1